



Email: info@shoalhavenmarine.com.au

Website: https://www.shoalhavenmarine.com.au/

29 Browns Road Nowra NSW 2541



250R

POA

Specifications

Boat Details

Price POA Boat Brand Mercury Model 250R Length 0.00

Year 2024 Category Boat Engines and Outboards

Hull Style Hull Type
Power Type Stock Number 0

Condition New State New South Wales

Suburb SOUTH NOWRA Engine Make Mercury

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.



Phone: 02 4422 3947

Email: info@shoalhavenmarine.com.au

Website: https://www.shoalhavenmarine.com.au/

29 Browns Road Nowra NSW 2541

Description

The 250R FourStroke pumps out 250 propshaft horsepower. The stout V-8 powerhead provides an astounding 53% increased displacement and up to 40% higher overall bottom-end torque than the legacy two-stroke 250XS it replaces. Transient spark calibration boosts torque by 7% for unmatched acceleration. Advanced Range Optimisation (ARO) automatically adjusts fuel delivery for up to 10% improvement in cruise-speed fuel efficiency. All of this on regular 91-RON Unleaded fuel, while maintaining a comparable weight to the 250 XS.Spesifications

- RATED HORSEPOWER (HP/KW)250/186
- BORE & STROKE (IN/MM)3.6 x 3.4/92 x 86
- IDLE RPM600
- MAX RPM AT FULL THROTTLE5800-6200
- CYLINDERS/ENGINE CONFIGURATIONV-8 (64 degree) with 32-valve Dual Overhead Cam (DOHC)
- DISPLACEMENT (LITER/CID)4.6/279
- INDUCTION SYSTEMPerformance-Tuned Long Runner Intake Manifold
- FUEL SYSTEMElectronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization
- FUEL REQUIREMENTSUnleaded Regular 87 Octane Minimum (R+M/2) or 90 RON
- IGNITION SYSTEMSmartCraft PCM 112 Digital Inductive
- CHARGING SYSTEM85-amp (1071 Watt)
- STARTINGElectric Start with SmartStart Protection
- LUBRICATION SYSTEMIntegrated wet sump
- OIL REQUIREMENTNMMA Certified FCW SAE 10W-30
- THROTTLE AND SHIFT CONTROLSMechanical
- MIDSECTION DESIGNTri-Ram Midsection with High-Durometer Elastomer Upper Mount and Solid Lower Mounts
- SHAFT LENGTH (IN./MM.)20/508
- GEARCASESport Master
- GEAR RATIO1.75:1
- WEIGHT (LBS./KGS.)520/236
- WARRANTY3-Year Limited

Engine Details

Engine Make

Mercury