



300 HP Verado

POA



Specifications

Boat Details

Price	POA	Boat Brand	Mercury
Model	300 HP	Length	0.00
Year	2020	Category	Boat Engines and Outboards
Hull Style		Hull Type	
Power Type		Stock Number	0
Condition	New	State	New South Wales
Suburb	SOUTH NOWRA	Engine Make	Mercury

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.

Description

The 300hp Verado premium outboard redefines the category with advanced engineering, innovative technology and refined operation. Representing the pinnacle of superior outboard design and performance Verado is unrivalled on the water. Built to power the largest boats for the boldest adventures, Verado engines boast advanced engineering and refined operation for boat owners who refuse to compromise. Every Verado feature is designed to deliver the ultimate, most satisfying on-water experience. The smooth, refined power of a V-8 4.6-litre powerhead delivers exhilarating acceleration and top speed to run offshore with confidence. Generous displacement and robust design provide uncompromising durability and reliability. The Mercury-exclusive Advanced MidSection (AMS) and under-cowl noise management features set the standard for smooth, quiet marine propulsion. Verado models now come with a 3+3=6 Year factory Warranty. ENGINE DETAILS

Lighter than its competition yet built to withstand the rigors of saltwater operation. For go-fast boats and commercial offshore operations that operate in rough seas or need more speed. Great for deck, inflatable rigid hull, inshore fishing, multi-species fishing, offshore fishing, and runabout cuddy boats, and tritoons. SPECIFICATIONS - 300 HP / kW

- 300 / 224

Engine type

- V-8

Displacement (CID/CC)

- 279 CID

Displacement (L)

- 4.6L

Cylinder Configuration

- V8 [64 degree] with Dual Overhead Cam [DOHC] and 32-valves

Full throttle RPM

- 5200-6000

Air induction

- Performance-Tuned Long-Runner Intake Manifold

Fuel induction system

- Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization

Alternator amp / Watt

- 115-amp (1449 Watt) with Idle Charge

Recommended fuel

- Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum

Recommended oil

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.

-
- NMMA Certified FCW SAE 10W-30

Engine protection operator warning system

- SmartCraft Engine Guardian

Starting

- Electric Start with SmartStart Protection

Controls

- Standard: Digital Throttle & Shift (DTS)

Steering

- Integrated Electro-Hydraulic Power-Steering

Shaft length

- 20" / 508 mm
- 25" / 635 mm
- 30" / 762 mm

Gearcase ratio

- 1.75:1 / 1.85:1

Dry weight *Lightest model available

- 600 lbs / 272 kgs

CARB star rating

- 3

Bore and stroke

- 3.6 in x 3.4 in / 92 mm x 86 mm

Ignition

- SmartCraft PCM 112 Digital Inductive

Cooling system

- Water-cooled with thermostat

Gear shift

- F-N-R

Gearcase options

- 5.44"

Trim system

- Power trim and tilt

Exhaust system

- Through prop

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.

Color

- Cold Fusion White
- Pearl Fusion White
- Phantom Black
- Warm Fusion White

Lubrication system

- Integrated wet sump

Oil Capacity

- 7.0 Quarts / 6.6 Liters

Maximum Trim Range

- 20° (-6° to 14°)

Maximum Tilt Range

- 73° (-6° to 67°)

Engine Details

Engine Make	Mercury
Displacement	4.6
Horse Power	300

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.